
H801


HF330


HP767


X3


RS01


AS365


AS365–C

CONTENTS

01–02 ····· H801

03–06 ····· HF330

07–08 ····· HP767

09–10 ····· X3

11–12 ····· RS01

13–16 ····· AS365

17–18 ····· AS365–C

CAMBODIA FACTORY

· Business Philosophy

Customer first, Innovation drives the future

· Mission

Build a image of premium, high-quality, innovative





Europe
E MARK CERTIFICATION

USA
DOT
DEPARTMENT OF TRANSPORT

E4-S

PAH FREE
REACH REGULATION

EUDR
EU Deforestation Regulation

ComfortMax HP



H801

A passenger car tire centered on outstanding safety and comfort.



- Low rolling resistance tire design. The application of new materials such as ultra- high strength steel wire and single-winding bead wire reduces rolling resistance while ensuring product rigidity.
- Multi-pitch tread pattern design, combined with optimized pitch sequencing, effectively reduces driving noise and improves ride-quality.
- Four drainage grooves provide excellent water evacuation performance.
- Optimized cross-sectional profile ensures more uniform stress distribution across all tire components, delivering better comfort and extended tire service life.

SIZE	XL/LT/C	LT	SS	PR	Standard Rim	Overall Diameter	Section Width	Max. Load	Max. Pressure	EU LABEL	EPRL CODE	EAN CODE	NOTE
						mm	mm	kg	kPa	(R/W/N)			
155/70R13		75	T	4	4.50B	548	157	387	300	CB69	√	√	
155/80R13		79	T	4	4.50B	578	157	437	300	CB69	√	√	
165/65R13		77	T	4	5.00B	544	170	412	300	CB69	√	√	
165/70R13		79	T	4	5.00B	562	170	437	300	CB69	√	√	
175/70R13		82	T	4	5.00B	576	177	475	300	CB69	√	√	
185/70R13		86	T	4	5.50B	590	189	530	300	CB69	√	√	*
155/65R14		75	T	4	4.5J	558	157	387	300	CB69	√	√	*
165/60R14		75	T	4	5J	554	170	387	300	CB69	√	√	
165/65R14		79	H	4	5J	570	170	437	300	CB69	√	√	
165/70R14		81	T	4	5J	588	170	462	300	CB69	√	√	
175/65R14		82	H	4	5J	584	177	475	300	CB69	√	√	
175/70R14		84	H	4	5J	602	177	500	300	CB69	√	√	
185/60R14		82	H	4	5.5J	578	189	475	300	CB69	√	√	
185/65R14		86	H	4	5.5J	596	189	530	300	CB69	√	√	
185/70R14		88	H	4	5.5J	616	189	560	300	CB69	√	√	
195/70R14		91	H	4	6J	630	201	615	300	CB69	√	√	
155/60R15		74	H	4	4.5J	567	157	375	300	CB69	√	√	*
175/65R15		84	H	4	5J	609	177	500	300	CB69	√	√	
175/55R15		77	H	4	5.5J	573	182	412	300	CB69	√	√	*
185/55R15		82	V	4	6J	585	194	475	300	CB69	√	√	
175/60R15		81	H	4	5J	591	177	462	300	CB69	√	√	
185/60R15		84	H	4	5.5J	603	189	500	300	CB69	√	√	
185/65R15		88	H	4	5.5J	621	189	560	300	CB69	√	√	
185/65R15	XL	92	H	4	5.5J	621	189	630	340	CB69	√	√	
195/50R15		82	V	4	6J	577	201	475	300	CB69	√	√	
195/55R15		85	V	4	6J	595	201	515	300	CB69	√	√	
195/60R15		88	V	4	6J	615	201	560	300	CB69	√	√	
195/65R15		91	V	4	6J	635	201	615	300	CB69	√	√	
195/65R15	XL	95	H	4	6J	635	201	690	340	CB69	√	√	
205/60R15		91	V	4	6J	627	209	615	300	CB69	√	√	
205/65R15		94	V	4	6J	647	209	670	300	CB69	√	√	
185/55R16		83	V	4	6J	610	194	487	300	CB69	√	√	
195/55R16	XL	91	V	4	6J	620	201	615	340	CB69	√	√	
195/60R16		89	H	4	6J	640	201	580	300	CB69	√	√	
205/55R16		91	V	4	6.5J	632	214	615	300	CB69	√	√	
205/60R16		92	V	4	6J	652	209	630	300	CB69	√	√	
205/65R16		95	H	4	6J	672	209	690	300	CB69	√	√	
215/60R16		95	V	4	6.5J	664	221	690	300	CB69	√	√	
225/60R16		98	H	4	6.5J	676	228	750	300	CB69	√	√	*
215/65R16		98	H	4	6.5J	686	221	750	300	CB69	√	√	
215/60R17		96	H	4	6.5J	690	221	710	300	CB69	√	√	

HeadKing



HF330

An ultra-high-performance tire with excellent handling. The special tread pattern design ensures outstanding performance on both dry and wet roads.



- Asymmetric tread pattern design provides excellent grip and handling on both dry and wet roads.
- Quiet design: multiple pitcheswith optimized sequencing, assisted by noise reduction blocksand special tread groove walls, effectively reduce tire pattern noise
- Shoulder wear indicatormarks allow the driver to easily check tire wear condition by measuring their depth.
- Triple wear bars ensure that tire performance remains unaffected even under severe wear conditions.

SIZE	XL/LT/C	LT	SS	PR	Standard Rim	Overall Diameter	Section Width	Max. Load	Max. Pressure	EU LABEL	EPRL CODE	EAN CODE	NOTE
						mm	mm	kg	kPa	(R/W/N)			
195/45R16	XL	84	V	4	6.5J	582	195	500	340	CB70	√	√	
195/50R16	XL	88	V	4	6J	602	201	560	340	CB70	√	√	
205/45ZR16	XL	87	W	4	7J	590	206	545	340	CB70	√	√	
205/50ZR16	XL	91	W	4	6.5J	612	214	615	340	CB70	√	√	*
205/55ZR16	XL	94	W	4	6.5J	632	214	670	340	CB70	√	√	
215/45ZR16	XL	90	W	4	7J	600	213	600	340	CB70	√	√	
215/55ZR16	XL	97	W	4	7J	642	226	730	340	CB70	√	√	
225/50ZR16	XL	96	W	4	7J	632	233	710	340	CB70	√	√	*
225/55ZR16	XL	99	W	4	7J	654	233	775	340	CB70	√	√	
195/45ZR17	XL	85	W	4	6.5J	608	195	515	340	CB70	√	√	*
205/40ZR17	XL	84	W	4	7.5J	596	212	500	340	CB70	√	√	
205/45ZR17	XL	88	W	4	7J	616	206	560	340	CB70	√	√	
205/50ZR17	XL	93	W	4	6.5J	638	214	650	340	CB70	√	√	
205/55ZR17	XL	95	W	4	6.5J	658	214	690	340	CB70	√	√	
215/40ZR17	XL	87	W	4	7.5J	604	218	545	340	CB70	√	√	
215/45ZR17	XL	91	W	4	7J	626	213	615	340	CB70	√	√	
215/50ZR17	XL	95	W	4	7J	648	226	690	340	CB70	√	√	
215/55ZR17	XL	98	W	4	7J	668	226	750	340	CB70	√	√	
225/45ZR17	XL	94	W	4	7.5J	634	225	670	340	CB70	√	√	
225/50ZR17	XL	98	W	4	7J	658	233	750	340	CB70	√	√	
225/55ZR17	XL	101	W	4	7J	680	233	825	340	CB70	√	√	
235/45ZR17	XL	97	W	4	8J	644	236	730	340	CB70	√	√	
235/50ZR17	XL	100	W	4	7.5J	668	245	800	340	CB70	√	√	
235/55ZR17	XL	103	W	4	7.5J	690	245	875	340	CB70	√	√	
245/40ZR17	XL	95	W	4	8.5J	628	248	690	340	CB70	√	√	*
245/45ZR17	XL	99	W	4	8J	652	243	775	340	CB70	√	√	
255/45ZR17	XL	102	W	4	8.5J	662	255	850	340	CB70	√	√	*
215/35ZR18	XL	84	Y	4	7.5J	607	218	500	340	CB70	√	√	*
215/40ZR18	XL	89	W	4	7.5J	629	218	580	340	CB70	√	√	*
215/45ZR18	XL	93	W	4	7J	651	213	650	340	CB70	√	√	
215/50ZR18	XL	96	W	4	7J	673	226	710	340	CB70	√	√	
225/40ZR18	XL	92	W	4	8J	637	230	630	340	CB70	√	√	
225/45ZR18	XL	95	W	4	7.5J	659	225	690	340	CB70	√	√	
225/50ZR18	XL	99	W	4	7J	683	233	775	340	CB70	√	√	
215/55ZR18	XL	99	W	4	7J	693	226	775	340	CB70	√	√	
225/55ZR18	XL	102	W	4	7J	705	233	850	340	CB70	√	√	
235/40ZR18	XL	95	W	4	8.5J	645	241	690	340	CB70	√	√	
235/45ZR18	XL	98	W	4	8J	669	236	750	340	CB70	√	√	
235/50ZR18	XL	101	W	4	7.5J	693	245	825	340	CB70	√	√	

SIZE	XL/LT/C	LT	SS	PR	Standard Rim	Overall Diameter	Section Width	Max. Load	Max. Pressure	EU LABEL	EPRL CODE	EAN CODE	NOTE
						mm	mm	kg	kPa	(R/W/N)			
245/40ZR18	XL	97	W	4	8.5J	653	248	730	340	CB70	√	√	
245/45ZR18	XL	100	W	4	8J	677	243	800	340	CB70	√	√	
245/50ZR18	XL	104	W	4	7.5J	703	253	900	340	CB70	√	√	*
255/40ZR18	XL	99	Y	4	9J	661	260	775	340	CB71	√	√	*
255/35ZR18	XL	94	Y	4	9J	635	260	670	340	CB71	√	√	*
255/45ZR18	XL	103	W	4	8.5J	687	255	875	340	CB71	√	√	
265/35ZR18	XL	97	W	4	9.5J	643	271	730	340	CB71	√	√	*
225/35ZR19	XL	88	W	4	8J	641	230	560	340	CB70	√	√	*
225/40ZR19	XL	93	W	4	8J	663	230	650	340	CB70	√	√	
235/35ZR19	XL	91	W	4	8.5J	647	241	615	340	CB70	√	√	
235/40ZR19	XL	96	W	4	8.5J	671	241	710	340	CB70	√	√	*
235/45ZR19	XL	99	W	4	8J	695	236	775	340	CB70	√	√	
235/55ZR19	XL	105	W	4	7.5J	741	245	925	340	CB70	√	√	
245/35ZR19	XL	93	W	4	8.5J	655	248	650	340	CB70	√	√	
245/40ZR19	XL	98	Y	4	8.5J	679	248	750	340	CB70	√	√	
245/45ZR19	XL	102	Y	4	8J	703	243	850	340	CB70	√	√	
255/35ZR19	XL	96	W	4	9J	661	260	710	340	CB70	√	√	
255/45ZR19	XL	104	W	4	8.5J	713	255	900	340	CB70	√	√	
265/30ZR19	XL	93	W	4	9.5J	643	271	650	340	CB71	√	√	*
275/30ZR19	XL	96	Y	4	9.5J	649	278	710	340	CB71	√	√	*
275/40ZR19	XL	105	W	4	9.5J	703	278	925	340	CB71	√	√	*
225/35ZR20	XL	90	W	4	8J	666	230	600	340	CB70	√	√	*
235/35ZR20	XL	92	W	4	8.5J	672	241	630	340	CB70	√	√	
245/35ZR20	XL	95	W	4	8.5J	680	248	690	340	CB70	√	√	
245/40ZR20	XL	99	Y	4	8.5J	704	248	775	340	CB70	√	√	
245/45ZR20	XL	103	Y	4	8J	728	243	875	340	CB70	√	√	
255/35ZR20	XL	97	W	4	9J	686	260	730	340	CB70	√	√	
315/35ZR20	XL	110	W	4	11J	728	320	1060	340	CB72	√	√	*
245/30ZR22	XL	92	W	4	8.5J	707	248	630	340	CB70	√	√	*
235/55ZR18	XL	104	W	4	7.5J	715	245	900	340	CB70	√	√	
255/55ZR18	XL	109	W	4	8J	737	265	1030	340	CB70	√	√	*
255/60R18	XL	112	V	4	7.5J	763	260	1120	340	CB70	√	√	
225/45R19	XL	96	W	4	7.5J	685	225	710	340	CB70	√	√	
225/55ZR19		99	W	4	7J	731	233	775	300	CB70	√	√	
255/40ZR19	XL	100	W	4	9J	687	260	800	340	CB70	√	√	
255/50ZR19	XL	107	W	4	8J	739	265	975	340	CB70	√	√	*
255/55R19	XL	111	W	4	8J	763	265	1090	340	CB70	√	√	*

SIZE	XL/LT/C	LT	SS	PR	Standard Rim	Overall Diameter	Section Width	Max. Load	Max. Pressure	EU LABEL	EPRL CODE	EAN CODE	NOTE
						mm	mm	kg	kPa	(R/W/N)			
285/45R19	XL	111	W	4	9.5J	739	285	1090	340	CB72	√	√	*
235/45ZR20	XL	100	W	4	8J	720	236	800	340	CB70	√	√	
235/55ZR20	XL	105	W	4	7.5J	766	245	925	340	CB70	√	√	*
245/50ZR20		102	W	4	7.5J	754	253	850	300	CB70	√	√	*
255/40ZR20	XL	101	Y	4	9J	712	260	825	340	CB70	√	√	
255/45ZR20	XL	105	W	4	8.5J	738	255	925	340	CB70	√	√	
255/50ZR20	XL	109	W	4	8J	764	265	1030	340	CB70	√	√	*
255/55ZR20	XL	110	W	4	8J	788	265	1060	340	CB70	√	√	*
265/45ZR20	XL	108	Y	4	9J	746	266	1000	340	CB70	√	√	*
265/50R20	XL	111	W	4	8.5J	774	277	1090	340	CB70	√	√	*
275/30ZR20	XL	97	Y	4	9.5J	674	278	730	340	CB70	√	√	
275/35ZR20	XL	102	W	4	9.5J	700	278	850	340	CB70	√	√	*
275/40ZR20	XL	106	W	4	9.5J	728	278	950	340	CB70	√	√	*
275/45ZR20	XL	110	W	4	9J	756	273	1060	340	CB70	√	√	*
285/50ZR20	XL	116	W	4	9J	794	297	1250	340	CB72	√	√	*
265/40ZR21	XL	105	W	4	9.5J	745	271	925	340	CB70	√	√	*
265/45ZR21		104	W	4	9J	771	266	900	300	CB70	√	√	*
275/45ZR21	XL	110	W	4	9J	781	273	1060	340	CB70	√	√	*
295/35ZR21	XL	107	Y	4	10.5J	739	301	975	340	CB72	√	√	*
325/30ZR21	XL	108	W	4	11.5J	729	331	1000	340	CB72	√	√	*
275/40ZR22	XL	107	Y	4	9.5J	779	278	975	340	CB70	√	√	*
285/35ZR22	XL	106	W	4	10J	759	290	950	340	CB72	√	√	*
295/30ZR22	XL	103	W	4	10.5J	737	301	875	340	CB72	√	√	*

PracticalMax SUV



HP767

A well-balanced urban SUV tire offering excellent high- speed stability, quiet comfort, and outstanding wet performance.



- Uniform rigidity tread block design enhances straight-line driving stability.
- Tread Pattern Groove Drainage Design, featuring four main grooves combined with continuous lateral grooves, provides superior water evacuation.
- Multi-pitch tread pattern design, combined with optimized pitch sequencing, effectively reduces noise caused by resonance of tread blocks and improves ride quality.
- Specially designed tread grooves further enhance anti- hydro-planing performance.
- More visually striking appearance.

SIZE	XL/LT/C	LT	SS	PR	Standard Rim	Overall Diameter	Section Width	Max. Load	Max. Pressure	EU LABEL	EPRL CODE	EAN CODE	NOTE
						mm	mm	kg	kPa	(R/W/N)			
235/75R15		105	H	4	6.5J	733	235	925	300	CB71	√	√	*
215/70R16		100	H	4	6.5J	708	221	800	300	CB71	√	√	
225/70R16		103	H	4	6.5J	722	228	875	300	CB71	√	√	*
235/60R16		100	H	4	7J	688	240	800	300	CB71	√	√	*
235/70R16		106	H	4	7J	736	240	950	300	CB71	√	√	*
245/70R16	XL	111	H	4	7J	750	248	1090	340	CB71	√	√	*
255/70R16		111	H	4	7.5J	764	260	1090	300	CB72	√	√	*
265/70R16		112	H	4	8J	778	272	1120	300	CB72	√	√	*
265/75R16		116	H	4	7.5J	804	267	1250	300	CB72	√	√	*
215/65R17		99	H	4	6.5J	712	221	775	300	CB71	√	√	
225/60R17		99	H	4	6.5J	702	228	775	300	CB71	√	√	
225/65R17		102	H	4	6.5J	724	228	850	300	CB71	√	√	
235/55R17		99	H	4	7.5J	690	245	775	300	CB71	√	√	*
235/65R17	XL	108	H	4	7J	738	240	1000	340	CB71	√	√	*
245/65R17	XL	111	H	4	7J	750	248	1090	340	CB71	√	√	*
265/65R17		112	H	4	8J	776	272	1120	300	CB72	√	√	
225/60R18		100	H	4	6.5J	727	228	800	300	CB71	√	√	*
235/50R18	XL	101	H	4	7.5J	693	245	825	340	CB71	√	√	*
235/55R18	XL	104	H	4	7.5J	715	245	900	340	CB71	√	√	*
235/60R18	XL	107	H	4	7J	739	240	975	340	CB71	√	√	
255/55R18	XL	109	V	4	8J	737	265	1030	340	CB72	√	√	*
265/60R18	XL	114	H	4	8J	775	272	1180	340	CB72	√	√	*

Concrossor AT



X3

An all-terrain off-road tire. While delivering on-road performance, it also provides excellent grip and traction in extreme conditions such as mountain roads, mud, and snow.

- Multi-directional groove and sipe combination design provides excellent traction performance in all driving directions.
- Variable-depth lateral groove design reduces pattern noise while increasing tread block strength.
- Special shoulder reinforcement design prevents tire damage caused by unpaved roads.
- Wavy shoulder design combined with prominent sidewall protrusions improves heat dissipation and sidewall impact resistance.



SIZE	XL/LT/C	LT	SS	PR	Standard Rim	Overall Diameter	Section Width	Max. Load	Max. Pressure	EU LABEL	EPRL CODE	EAN CODE	M+S	3PMSF	NOTE
						mm	mm	kg	kPa	(R/W/N)					
265/70R15		112	T	4	8J	753	272	1120	300	CC72	√	√	√		*
P215/70R16		100	T	4	6.5J	708	221	800	300	CC71	√	√	√		*
P225/70R16		103	T	4	6.5J	722	228	875	300	CC71	√	√	√		*
P235/70R16		106	T	4	7J	736	240	950	300	CC71	√	√	√		
P245/70R16	XL	111	T	4	7J	750	248	1090	340	CC71	√	√	√		
P255/70R16		111	T	4	7.5J	764	260	1090	300	CC72	√	√	√		*
P275/70R16		114	T	4	8J	792	279	1180	300	CC72	√	√	√		*
235/65R17		104	T	4	7J	738	240	900	300	CC71	√	√	√		*
P255/65R17		110	T	4	7.5J	764	260	1060	300	CC72	√	√	√		*
P265/65R17		112	T	4	8J	776	272	1120	300	CC72	√	√	√		
255/60R18	XL	112	T	4	7.5J	763	260	1120	340	CC72	√	√	√		*
P265/60R18		110	T	4	8J	775	272	1060	300	CC72	√	√	√		
P285/60R18		116	H	4	8.5J	799	292	1250	300	CC72	√	√	√		*
P285/50R20	XL	116	Q	4	9J	794	297	1250	340	CC72	√	√	√		*
31X10.5R15LT		109	Q	6C	8.5J	775	268	1030	350	CC72	√	√	√		
LT215/75R15		100/97	S	6	6J	703	216	800/730	350	CC72	√	√	√		*
LT225/70R15		112/110	R	8	6.5J	697	228	1120/1060	450	CC72	√	√	√		*
LT235/75R15		104/101	S	6	6.5J	733	235	900/825	350	CC72	√	√	√		*
LT225/75R16		115/112	S	10	6J	744	223	1215/1120	550	CC72	√	√	√		
LT235/70R16		110/107	S	8	7J	736	240	1060/975	450	CC72	√	√	√		*
LT235/85R16		120/116	Q	10	6.5J	806	235	1400/1250	550	CC72	√	√	√		
LT265/70R16		117/114	T	8	8J	778	272	1285/1180	450	CC72	√	√	√		*
LT265/75R16		123/120	S	10	7.5J	804	267	1550/1400	550	CC72	√	√	√		
LT285/75R16		126/123	S	10	8J	834	286	1700/1550	550	CC72	√	√	√		*
LT235/65R17		109/105	R	8	7J	738	240	1030/925	450	CC72	√	√	√		*
LT245/65R17		117/114	R	10	7J	750	248	1285/1180	550	CC72	√	√	√		*

DurableMax LT



RS01

RS01 is a light truck tire for business use,which can meet the overweight test under various extremaly harsh conditions. It is specially designed to improve the business operation income.



- Imported ultra- fine carbon black significantly improves wear resistance while effectively reducing rolling resistance.
- "Z" - shaped main groove design enhances water drainage while ensuring road grip.
- Closed shoulder groove design reduces noise.
- Widened tread design optimizes contact patch shape and pressure distribution for extended service life.

SIZE	LT	SS	PR	Standard Rim	Overall Diameter	Section Width	Max. Load	Max. Pressure	EU LABEL	EPRL CODE	EAN CODE	M+S	3PMSF	NOTE
					mm	mm	kg	kPa	(R/W/N)					
5 .50R13LT	94/92	Q	12	4.00B	620	160	670/630	670	CB71	√	√	√		*
6.00R16LT	103/101			4.5E	730	170	875/825		CB71	√	√	√		*
6 .50R16LT	110/105	N	12	5.50F	750	185	1060/925	670	CB71	√	√	√		*
7 .00R16C	115/110	N	12	5.50F	775	200	1215/1060	670	CB71	√	√	√		*
7 .50R16C	122/118	N	14	6.00G	805	215	1500/1320	770	CB71	√	√	√		*
155R13C	90/88			4.50B	578	157	600/560	450	CB71	√	√	√		*
175/65R14C	90/88	T	6	5J	584	177	600/560	350	CB71	√	√	√		*
175/70R14C	95/93	T	8	5J	602	177	690/650	450	CB71	√	√	√		
175R14C	99/98	T	8	5J	634	178	775/750	450	CB71	√	√	√		*
185R14C	102/100	T	8	5.5J	650	188	850/800	450	CB71	√	√	√		
195R14C	106/104	T	8	5.5J	666	198	950/900	450	CB71	√	√	√		
195/70R15C	104/102	T	8	6J	655	201	900/850	450	CB71	√	√	√		
215/65R15C	104/102	T	8	6.5J	661	221	900/850	450	CB71	√	√	√		
215/70R15C	109/107	T	8	6.5J	683	221	1030/975	450	CB71	√	√	√		
225/70R15C	112/110	T	8	6.5J	697	228	1120/1060	450	CB71	√	√	√		
185/75R16C	104/102	T	8	5J	684	184	900/850	450	CB71	√	√	√		
195/65R16C	104/102	T	8	6J	660	201	900/850	450	CB71	√	√	√		
195/75R16C	110/108	T	10	5.5J	698	196	1060/1000	525	CB71	√	√	√		
205/65R16C	107/105	T	8	6J	672	209	975/925	450	CB71	√	√	√		
205/75R16C	113/111	T	10	5.5J	714	203	1150/1090	550	CB71	√	√	√		
215/60R16C	108/106	T	8	6.5J	664	221	1000/950	450	CB71	√	√	√		
215/65R16C	109/107	T	8	6.5J	686	221	1030/975	450	CB71	√	√	√		
215/70R16C	108/106	T	8	6.5J	708	221	1000/950	450	CB71	√	√	√		*
215/75R16C	116/114	T	10	6J	728	216	1250/1180	550	CB71	√	√	√		
225/65R16C	112/110	T	8	6.5J	698	228	1120/1060	450	CB71	√	√	√		
235/65R16C	121/119	T	12	7J	712	240	1450/1360	575	CB71	√	√	√		

A/S Superb



AS365

Anall-seasontirewithexcellentall-aroundper-formance.



- "V"-shaped lateral groove design provides excellent snow evacuation while improving braking performance on icy and snowy-roads.
- Interconnected groove design—connecting the shoulder-grooves to the central main grooves—achieves optimal water drainage and ensures driving safety.
- The 3D ultra-thin tread groove design effectively improves grip on ice and snow while maintaining tread block shape stability during acceleration, braking, and cornering, thereby enhancing handling and braking performance on icy and snowy roads.
- Multi-pitch tread pattern design, combined with optimized pitch sequencing, effectively reduces driving noise and improves ride-quality.

SIZE	XL/LT/C	LT	SS	PR	Standard Rim	Overall Diameter	Section Width	Max. Load	Max. Pressure	EU LABEL	EPRL CODE	EAN CODE	M+S	3PMSF	NOTE
						mm	mm	kg	kPa	(R/W/N)					
145/70R13		71	T	4	4.50B	534	150	345	300	CB70	√	√	√	√	
155/65R13		73	T	4	4.50B	532	157	365	300	CB70	√	√	√	√	
155/70R13		75	T	4	4.50B	548	157	387	300	CB70	√	√	√	√	
155/80R13		79	T	4	4.50B	578	157	437	300	CB70	√	√	√	√	
165/70R13		79	T	4	5.00B	562	170	437	300	CB70	√	√	√	√	
175/70R13		82	T	4	5.00B	576	177	475	300	CB70	√	√	√	√	
155/65R14		75	T	4	4.5J	558	157	387	300	CB70	√	√	√	√	*
165/60R14	XL	79	H	4	5J	554	170	437	340	CB70	√	√	√	√	
165/65R14		79	T	4	5J	570	170	437	300	CB70	√	√	√	√	
165/70R14		81	T	4	5J	588	170	462	300	CB70	√	√	√	√	
175/65R14		82	T	4	5J	584	177	475	300	CB70	√	√	√	√	
175/65R14	XL	86	H	4	5J	584	177	530	340	CB70	√	√	√	√	
175/70R14	XL	88	T	4	5J	602	177	560	340	CB70	√	√	√	√	
185/60R14		82	H	4	5.5J	578	189	475	300	CB70	√	√	√	√	
185/65R14		86	H	4	5.5J	596	189	530	300	CB70	√	√	√	√	
185/70R14		88	H	4	5.5J	616	189	560	300	CB70	√	√	√	√	
195/70R14		91	T	4	6J	630	201	615	300	CB71	√	√	√	√	
165/65R15		81	H	4	5J	595	170	462	300	CB70	√	√	√	√	*
175/65R15		84	H	4	5J	609	177	500	300	CB70	√	√	√	√	
185/55R15		82	H	4	6J	585	194	475	300	CB70	√	√	√	√	
185/55R15	XL	86	H	4	6J	585	194	530	340	CB70	√	√	√	√	
185/60R15	XL	88	H	4	5.5J	603	189	560	340	CB70	√	√	√	√	
185/65R15		88	H	4	5.5J	621	189	560	300	CB70	√	√	√	√	
185/65R15	XL	92	H	4	5.5J	621	189	630	340	CB70	√	√	√	√	
215/65R15		96	H	4	6.5J	661	221	710	300	CB71	√	√	√	√	
195/45R16	XL	84	V	4	6.5J	582	195	500	340	CB71	√	√	√	√	
195/50R16	XL	88	V	4	6J	602	201	560	340	CB71	√	√	√	√	
205/45R16		87	W	4	7J	590	206	545	300	CB71	√	√	√	√	*
205/50R16	XL	91	W	4	6.5J	612	214	615	340	CB71	√	√	√	√	*
225/45R17	XL	94	V	4	7.5J	634	225	670	340	CB71	√	√	√	√	
215/45R16	XL	90	V	4	7J	600	213	600	340	CB71	√	√	√	√	
195/65R15	XL	95	H	4	6J	635	201	690	340	CB71	√	√	√	√	
195/65R15		91	V	4	6J	635	201	615	300	CB71	√	√	√	√	
195/55R16	XL	91	V	4	6J	620	201	615	340	CB71	√	√	√	√	
195/60R16		89	H	4	6J	640	201	580	300	CB71	√	√	√	√	
205/55R16		91	V	4	6.5J	632	214	615	300	CB71	√	√	√	√	
205/55R16	XL	94	V	4	6.5J	632	214	670	340	CB71	√	√	√	√	
205/60R16	XL	96	V	4	6J	652	209	710	340	CB71	√	√	√	√	
215/55R16	XL	97	V	4	7J	642	226	730	340	CB71	√	√	√	√	

SIZE	XL/LT/C	LT	SS	PR	Standard Rim	Overall Diameter	Section Width	Max. Load	Max. Pressure	EU LABEL	EPRL CODE	EAN CODE	M+S	3PMSF	NOTE
						mm	mm	kg	kPa	(R/W/N)					
215/60R16	XL	99	H	4	6.5J	664	221	775	340	CB71	√	√	√	√	
215/65R16	XL	102	H	4	6.5J	686	221	850	340	CB71	√	√	√	√	
205/40ZR17	XL	84	W	4	7.5J	596	212	500	340	CB71	√	√	√	√	
205/45ZR17	XL	88	W	4	7J	616	206	560	340	CB71	√	√	√	√	
205/50R17	XL	93	V	4	6.5J	638	214	650	340	CB71	√	√	√	√	
205/55ZR17	XL	95	W	4	6.5J	658	214	690	340	CB71	√	√	√	√	
215/40ZR17	XL	87	W	4	7.5J	604	218	545	340	CB71	√	√	√	√	
215/45ZR17	XL	91	W	4	7J	626	213	615	340	CB71	√	√	√	√	
215/50ZR17	XL	95	W	4	7J	648	226	690	340	CB71	√	√	√	√	
215/55ZR17	XL	98	W	4	7J	668	226	750	340	CB71	√	√	√	√	
215/60R17		96	H	4	6.5J	690	221	710	300	CB71	√	√	√	√	
225/50ZR17	XL	98	W	4	7J	658	233	750	340	CB71	√	√	√	√	
225/55ZR17	XL	101	W	4	7J	680	233	825	340	CB71	√	√	√	√	
225/60R17		99	H	4	6.5J	702	228	775	300	CB71	√	√	√	√	
235/45ZR17	XL	97	W	4	8J	644	236	730	340	CB71	√	√	√	√	
235/55ZR17		99	W	4	7.5J	690	245	775	300	CB71	√	√	√	√	
235/65R17		104	H	4	7J	738	240	900	300	CB71	√	√	√	√	*
215/55R18		95	V	4	7J	693	226	690	300	CB71	√	√	√	√	
225/40ZR18	XL	92	W	4	8J	637	230	630	340	CB71	√	√	√	√	
225/45R18	XL	95	V	4	7.5J	659	225	690	340	CB71	√	√	√	√	
225/50ZR18	XL	99	W	4	7J	683	233	775	340	CB71	√	√	√	√	
225/55R18	XL	102	H	4	7J	705	233	850	340	CB71	√	√	√	√	
235/40ZR18	XL	95	W	4	8.5J	645	241	690	340	CB71	√	√	√	√	
235/45ZR18	XL	98	W	4	8J	669	236	750	340	CB71	√	√	√	√	
235/55R18	XL	104	V	4	7.5J	715	245	900	340	CB71	√	√	√	√	*
235/60R18	XL	107	V	4	7J	739	240	975	340	CB71	√	√	√	√	
245/40ZR18	XL	97	W	4	8.5J	653	248	730	340	CB71	√	√	√	√	
245/45ZR18	XL	100	W	4	8J	677	243	800	340	CB71	√	√	√	√	
225/40ZR19	XL	93	W	4	8J	663	230	650	340	CB71	√	√	√	√	
225/45ZR19	XL	96	W	4	7.5J	685	225	710	340	CB71	√	√	√	√	
225/55R19	XL	99	V	4	7J	731	233	775	340	CB71	√	√	√	√	*

SIZE	XL/LT/C	LT	SS	PR	Standard Rim	Overall Diameter	Section Width	Max. Load	Max. Pressure	EU LABEL	EPRL CODE	EAN CODE	M+S	3PMSF	NOTE
						mm	mm	kg	kPa	(R/W/N)					
235/35ZR19	XL	91	W	4	8.5J	647	241	615	340	CB71	√	√	√	√	
235/45ZR19	XL	99	W	4	8J	695	236	775	340	CB71	√	√	√	√	
245/40ZR19	XL	98	W	4	8.5J	679	248	750	340	CB71	√	√	√	√	
245/45ZR19	XL	102	W	4	8J	703	243	850	340	CB71	√	√	√	√	
255/35ZR19	XL	96	W	4	9J	661	260	710	340	CB71	√	√	√	√	
255/40ZR20	XL	101	W	4	9J	712	260	825	340	CB71	√	√	√	√	
255/45ZR20	XL	105	W	4	8.5J	738	255	925	340	CB71	√	√	√	√	*
225/55R16	XL	99	W	4	7J	654	233	775	340	CB71	√	√	√	√	
225/60R16		102	V	4	6.5J	676	228	850	300	CB71	√	√	√	√	*
225/65R17		106	V	4	6.5J	724	228	950	300	CB71	√	√	√	√	*
235/50R18		101	W	4	7.5J	693	245	825	300	CB71	√	√	√	√	*
235/55R19	XL	105	W	4	7.5J	741	245	925	340	CB71	√	√	√	√	
225/45ZR17	XL	94	W	4	7.5J	634	225	670	340	CB71	√	√	√	√	
225/45ZR17		91	W	4	7.5J	634	225	615	300	CB71	√	√	√	√	
235/55R17		99	V	4	7.5J	690	245	775	300	CB71	√	√	√	√	
255/55R18		105	V	4	8J	737	265	925	300	CB71	√	√	√	√	
185/55R14	XL	84	T	4	6J	560	194	500	340	CB70	√	√	√	√	
185/60R14	XL	86	H	4	5.5J	578	189	530	340	CB70	√	√	√	√	
195/50R15		82	V	4	6J	577	201	475	300	CB71	√	√	√	√	
195/50R15	XL	86	H	4	6J	577	201	530	340	CB71	√	√	√	√	
195/50R16	XL	92	V	4	6J	602	201	630	340	CB71	√	√	√	√	
195/55R15		85	V	4	6J	595	201	515	300	CB71	√	√	√	√	
195/55R15	XL	89	H	4	6J	595	201	580	340	CB71	√	√	√	√	
195/60R15		88	V	4	6J	615	201	560	300	CB71	√	√	√	√	
195/60R15	XL	92	V	4	6J	615	201	630	340	CB71	√	√	√	√	
205/65R15	XL	99	H	4	6J	647	209	775	340	CB71	√	√	√	√	
205/65R15		94	V	4	6J	647	209	670	300	CB71	√	√	√	√	
215/55R17	XL	98	V	4	7J	668	226	750	340	CB71	√	√	√	√	
215/55R18	XL	99	V	4	7J	693	226	775	340	CB71	√	√	√	√	
215/55R18	XL	99	W	4	7J	693	226	775	340	CB71	√	√	√	√	
225/55R17	XL	101	V	4	7J	680	233	825	340	CB71	√	√	√	√	

A/S Superb LT



AS365-C

An all-season commercial LT/C tire with excellent all-around performance,offering good water drainage and snow braking capability.



- The tread compound uses foamed rubber technology, which absorbs moisture on ice and removes the water film; at the same time, it continuously keeps the rubber soft and inhibits performance degradation.
- The symmetric tread pattern design provides more uniform tire stress distribution, while the three-dimensional drainage groove design quickly evacuates water from the tread surface at high speeds, greatly reducing the risk of hydroplaning and maximizing wet grip.
- The 3D ultra-thin tread groove design effectively improves grip on ice and snow while maintaining tread block shape stability during acceleration, braking, and cornering, thereby enhancing handling and braking performance on icy and snowy roads.
- Multi-pitch tread pattern design, combined with optimized pitch sequencing, effectively reduces driving noise and improves ride-quality

SIZE	XL/LT/C	LT	SS	PR	Standard Rim	Overall Diameter	Section Width	Max. Load	Max. Pressure	EU LABEL	EPRL CODE	EAN CODE	M+S	3PMSF	NOTE
						mm	mm	kg	kPa	(R/W/N)					
175/65R14C		90/88	T		5J	584	177	600/560	375	CB71	√	√	√	√	*
175/70R14C		95/93	T		5J	602	177	690/650	375	CB71	√	√	√	√	*
185/65R15C		97/95	S		5.5J	621	189	730/690	375	CB71	√	√	√	√	
195/70R15C		104/102	S		6J	655	201	900/850	450	CB71	√	√	√	√	
205/70R15C		106/104	S		6J	669	209	950/900	450	CB71	√	√	√	√	
215/65R15C		104/102	T		6.5J	661	221	900/850	375	CB71	√	√	√	√	
215/70R15C		109/107	R		6.5J	683	221	1030/975	450	CB71	√	√	√	√	
225/70R15C		112/110	S		6.5J	697	228	1120/1060	450	CB71	√	√	√	√	
185/75R16C		104/102	S		5J	684	184	900/850	475	CB71	√	√	√	√	*
195/60R16C		99/97	H		6J	640	201	775/730	375	CB71	√	√	√	√	
195/65R16C		104/102	T		6J	660	201	900/850	475	CB71	√	√	√	√	
195/75R16C		107/105	S		5.5J	698	196	975/925	475	CB71	√	√	√	√	
205/65R16C		107/105	T		6J	672	209	975/925	475	CB71	√	√	√	√	
205/75R16C		113/111	S		5.5J	714	203	1150/1090	525	CB71	√	√	√	√	
215/60R16C		103/101	T		6.5J	664	221	875/825	375	CB71	√	√	√	√	*
215/65R16C		109/107	T		6.5J	686	221	1030/975	475	CB71	√	√	√	√	
215/75R16C		113/111	S		6J	728	216	1150/1090	475	CB71	√	√	√	√	
225/65R16C		112/110	S		6.5J	698	228	1120/1060	475	CB71	√	√	√	√	
225/75R16C		121/120	R		6J	744	223	1450/1400	575	CB71	√	√	√	√	
235/65R16C		115/113	R		7J	712	240	1215/1150	475	CB71	√	√	√	√	